

PVE3250 Series Valves

Sherwood's PVE3250 Propylene Series is designed for applications in production welding and cutting, and supplying of fuel gases.

Features

- CG-7 Safety complies with CGA Technical Bulletin TB 27
- Conforms to UL® Standard 1769
- For use in up to 100-lb. LPG capacity cylinders
- Offered with and without liquid gauge and dip tube

Special Features for PVE3250R

- Compatible with both propane and propylene, 4BW240 and 4BW260 cylinders
- Includes replaceable PRV (CGA 5-1.1 recommends replacing every 10 years)
- Tamper-resistant bonnet



PVE3250R-435

PVE3250CLG435

PVE446B

Ordering Information:

Sherwood Part Number	Cylinder Type	Outlet Connection	Inlet Connection	Start to Discharge Setting (PSIG)	Special Features
PVE3250C-435	4B260, 4BA260, 4BW260	POL (CGA 510)	¾"-14 NGT	435-520	—
PVE3250CLG435*	4B260, 4BA260, 4BW260	POL (CGA 510)	¾"-14 NGT	435-520	Liquid Level Gauge
PVE3250CLG435-XX.X**	4B260, 4BA260, 4BW260	POL (CGA 510)	¾"-14 NGT	435-520	Liquid Level Gauge, Dip Tube
PVE3250R-435	4B260, 4BA260, 4BW260, 4BW240	POL (CGA 510)	¾"-14 NGT	435-480	Replaceable CG-7 Pressure-Relief Device
PVE446B	4B260, 4BA260, 4BW260	—	1"	435-520	Relief Valve for Propylene Service Only

* Diptube to be installed by customer

** XX.X specify length of diptube relative to cylinder size

Repair Kits

3250-8LH-KIT	Bonnet Assembly Kit
3250R-10-KIT	50 Replaceable Pressure-Relief Devices for PVE3250R-435
TL3250R	Tool for Replaceable CG-7



TL3250R



888.508.2583
 specgas@sherwoodvalve.com
 www.sherwoodvalve.com